

SVAN 977

Sound & Vibration Analyser

The SVAN 977 is the next generation of Class 1 sound & vibration instruments and is designed to meet the needs of both environmental monitoring and occupational health and safety monitoring specialists. Its exceptional hardware design also enables the measurement of ultra sound frequencies in the 40 kHz band.

The SVAN 977 provides broad-band results with all standard weighting filters and also offers an incredible time-history logging capability providing broad-band results and spectra with adjustable logging steps.

Audio recording can be performed simultaneously with time-history logging as either a separate wave file or as an audio events inside time-history files. This solution enables noise source recognition and data post-processing. Manual and automatic triggering of audio recording is also available. Measurement results are recorded in three acoustic or vibration profiles enabling measurements to be performed with 3 different filters

(e.g. A, C, Z) and 3 different detector time constants (e.g. Fast, Slow, Impulse).

Measurement data is stored on a microSD card and can be easily downloaded to a PC using SvanPC++ software over either USB or RS 232 interfaces.

The powerful DSP (digital signal processor) used in the SVAN 977 instrument can simultaneously operate in meter mode and perform real-time 1/1 or 1/3 octave analysis including statistical calculations. Additional functions like FFT analysis and Rotation Speed Measurement are also available.

The instrument is powered by four AA standard or rechargeable NiMH batteries (separate charger is required), from an external DC power source or USB interface. The robust and light weight design accomplishes the exceptional features of this instrument.

FEATURES

- Class 1 IEC 61672:2002 sound level measurements
- Dedicated for:
 - general acoustic measurements
 - environmental noise monitoring
 - ultra sound measurements in 40 kHz band
 - general vibration measurements (acceleration, velocity and displacement)
 - hand-arm vibration measurements
- Three parallel independent profiles
- 1/1 or 1/3 octave real-time analysis (optional)
- FFT analysis (optional)
- Time-domain signal recording & audio events recording (optional)
- Reverberation time measurements (optional)
- Advanced Data Logger including spectral analysis
- microSD card providing almost unlimited logging capacity
- Bluetooth™ interface (version dependent)
- All weather microphone protection kit designed for community and airport noise monitoring (optional)
- OLED color display with super brightness and contrast
- Hand held, light weight and robust case
- Easy to use



TECHNICAL SPECIFICATIONS

SOUND LEVEL METER & ANALYSER

Standards	Class 1: IEC 61672-1:2002
Meter Mode	SPL, L_{eq} , SEL, L_{den} , L_{m3} , L_{m5} , Statistics - L_n (L_1 - L_{99}), L_{Max} , L_{Min} , L_{Peak}
Analyser	Simultaneous measurement in three profiles with independent set of filters and detectors 1/1 or optional 1/3 octave ¹ real-time analysis meeting Type 1 requirements of IEC 61260 FFT ¹ real-time analysis 1600 lines, up to 20.0 kHz band (option) Reverberation time analysis in 1/3 octave bands (RT 60 option)
Weighting Filters	A, B, C, Z
RMS Detector	Digital True RMS detector with Peak detection, resolution 0.1 dB
Time constants	Slow, Fast, Impulse
Microphone	ACO 7052E, 35 mV/Pa, prepolarised 1/2" condenser microphone
Preamplifier	SV 12L IEPE preamplifier
Linear Operating Range	25 dBA - 140 dBA Peak (in accordance to IEC 61672)
Total Dynamic Measurement Range	15 dBA RMS - 140 dBA Peak (typical from noise floor to the maximum level)
Dynamic Range	> 110 dBA RMS
Internal Noise Level	less than 15 dBA RMS
Frequency Range	10 Hz ÷ 40 kHz (microphone dependent)
Statistics	L_n (L_1 - L_{99}), complete histogram in meter mode
Data Logger	Time-history logging of summary results, spectra with adjustable logging steps
Audio Events Recording	Audio records to time-history data or wav format on demand with selectable band and recording period

VIBRATION LEVEL METER & ANALYSER

Standards	ISO 10816-1
Meter Mode	RMS, MAX, Peak, Peak-Peak
Analyser	Simultaneous measurement in three profiles with independent set of filters and detectors 1/1 or optional 1/3 octave ¹ real-time analysis FFT ¹ analysis 1600 lines, up to 20.0 kHz band (option) RPM ¹ rotation speed measurement parallel to the vibration measurement (option)
Filters	HP1, HP3, HP10, Vel1, Vel3, Vel10, VelMF, Dil1, Dil3, Dil10
RMS Detector	Digital True RMS detector with Peak detection, resolution 0.1 dB Time constants: from 100 ms to 10 s
Accelerometer (option)	Any IEPE accelerometer
Measurement Range	Transducer dependent
Frequency Range	1.0 Hz ÷ 40 kHz (transducer dependent)

BASIC DATA

Input	IEPE type (TNC connector)	
Self-vibration Monitoring	Built-in	
Dynamic Range	> 110 dB	
Frequency Range	1.0 Hz ÷ 22.4 kHz (sampling rate 48 kHz) or 44.0 kHz (sampling 96 kHz)	
Data Logger ¹	Time-history logging with adjustable logging steps Time-domain signal recording and audio events recording function to microSD card	
Display	Super contrast (10000:1) OLED 2.4" colour display (320 x 240 pixels)	
Memory	MicroSD card 4 GB (included)	
Interfaces	USB 2.0 Client, Bluetooth (optional), RS 232 (with SV 55 option) External I/O - AC output (1 V Peak) or Digital Input/Output (Trigger - Pulse)	
Power Supply	Four AA batteries SA 17A external battery pack (option) External power supply USB interface	operation time > 8 h ÷ 12 h (4.8 V / 2.6 Ah) ² operation time > 24 h (option) ² 6 V/500 mA DC ÷ 15 V/250 mA DC 500 mA HUB
Environmental Conditions	Temperature Humidity	from -10 °C to 50 °C up to 90 % RH, non-condensed
Dimensions	305 x 79 x 39 mm (with microphone and preamplifier)	
Weight	Approx. 0.6 kg with batteries	

¹each function parallel to the meter mode ²depends on instrument operation mode

Continuous product development and innovation are the policy of our company. Therefore, we reserve the right to change the specifications without prior notice.

DISTRIBUTOR: _____



SVANTEK

SVANTEK Sp. z o. o.

ul. Strzygłowska 81

04-872 WARSAW, POLAND

phone/fax (+48) 22 51 88 320, (+48) 22 51 88 312

http://www.svantek.com e-mail: office@svantek.com.pl

